

SFXSA Acoustic detail at defined frequencies.

Frequency Hz	Dn,e dB									
	2500EA									5000EA
	V75 / C75	V75 / C50	V75 / Std. Canopy	V50 / C25	V50 / Std. Canopy	V25 /C25	V25 / Std. Canopy	Std. Vent / C25	Std. Vent / C75	V75 / C75 5000EA
100	37	40.2	37.8	37.9	34.4	37.8	35.9	35.7	37.8	37.5
125										
160										
200	37	37.2	36.5	37.7	36.8	37.6	37.6	37.7	36.2	35.4
250										
315										
400	36.1	34.4	34.8	33.4	34.5	34.4	36.3	36.1	34.5	32.1
500										
630										
800	46.9	42.8	39.5	36.3	35.9	32.1	31.8	32.1	41.9	39.8
1000										
1250										
1600	49.2	50.1	41.5	47.1	40.8	42.4	36.8	37.1	38.5	46.1
2000										
2500										
3150	55.2	52.8	44.8	49.2	41.6	48.8	40.4	38.9	42	59.7
4000										
5000										
6300+	61.3	62.9	53.8	57	51	55.4	47.8	47.8	52.7	58
8000+										
10000+										

Open	Rating D n.e.w.	44	42	40	39	38	36	35	35	39	40
Closed		55	55	53	55	55	55	54	55	55	51