

Capture

Window safety restrictor

Suitable for PVCu, Aluminium & Timber

Capture is an automatically engaging spring-loaded window safety restrictor for use on side and top hung windows to limit opening. Capture is supplied in austenitic steel.

Various pin heights are available to suit all cavity sizes and can be retrofitted.

Features & Benefits

- Automatically engages
- Easy to fit
- No key or tools required to de-restrict
- Three variations available
- Various pin heights
- Suits most cavity sizes
- Can be retrofitted
- Austenitic stainless steel for improved corrosion resistance
- Suitable for aluminium, PVCu and Timber windows (left and right hand versions)



Details

Product	Product Code
Capture Restrictor LH - 66mm (Short)	TN1121
Capture Restrictor RH - 66mm (Short)	TN1120
Capture Restrictor LH - 110mm (Medium)	TN1131
Capture Restrictor RH - 110mm (Medium)	TN1130
Capture Restrictor LH - 145mm (Long)	TN1141
Capture Restrictor RH - 145mm (Long)	TN1140
Capture Restrictor Pin - 9.5mm	TN1122
Capture Restrictor Pin - 10.5mm	TN1123
Capture Restrictor Pin - 11.5mm	TN1124
Capture Restrictor Pin - 14.5mm	TN1125
Capture Restrictor Pin - 16.5mm	TN1126

Manufactured from

Austenitic stainless steel 304 to BS EN 10088-2 Grade 1.4301

Recommended screws

Designed to accept a maximum screw diameter Ø4.8mm with a maximum head diameter Ø8mm

NOTE: All screws must be stainless steel

Performance

Please contact us for the latest test results.

Finishes

Natural

Standards

Tested in accordance with BS 6375 Part 2:2009
BS EN 1670 Grade 5

More information

Refer to separate fitting and operating instructions
enquiries@titon.com / 01206 713801

